NSN 5999-00-617-5672



Delay Line - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5999-00-617-5672

Body Style:
Rectangular, bracketed

Hole Diameter:
0.250 inches

Overall Length:
2.375 inches

Frequency Rating:
Not rated

Adjustment Device Quantity:
1

Adjustment Device Drive Type:
Slotted screw

Body Length:
1.391 inches

Body Width:

Body Width:
1.063 inches
Individual Section Quantity:
1

Operating Tempurature Range:

+0.0 to 75.0 degrees celsius

Mounting Facility Quantity:

8

Voltage Rating:

Not rated

Material And Location:

Any acceptable

Surface Treatment And Location:

Any acceptable

Input Impedance Rating:

Not rated

Output Impedance Rating:

Not rated

Frequency Bandwidth:

600.0 kilohertz

Body Depth:

6.000 inches

Mounting Facility:

Unthreaded hole

Attenuation In Decibels:

1.000

Signal Delay Method:

Transmission line

NSN 5999-00-617-5672

Delay Line - Page 2 of 2



| Delay Time Variation Method: |
|---------------------------------------|
| Variable |
| Section Delay Time: |
| 2.700 microseconds single section |
| Delay Time Variation Per Deg Celsius: |
| Not rated |
| Pulse Rise Time Rating: |
| 0.6 microseconds |
| Terminal Type And Quantity: |
| 8 turret |
| Fsc Application Data: |
| Test except specially designed |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| Fiig: |

A32100