## NSN 5999-00-631-3066

Relay-switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-00-631-3066

2.830 inclust         Overall Height:         4.520 inclust         Overall Width:         2.570 inclust         Current Type:         Dc         Switch Type:         Relay         Contact Form Arrangement:         2c         Mouning Configuration:         Four tapped holes on back plate         Action Type:         Time delay         Relay Type:         Time delay         Contact Current Type:         Dc         Maximum Voltage Rating In Volts:         250.0         Coll Current Type:         Dc         Mouth Contact Form Arrangement:         1700         Switch Contact Form Arrangement:         1701         Solo         Switch Contact Form Arrangement:         1702         Contact Maximum Voltage Rating In Volts:         17030         Switch Contact Form Arrangement:         1704         Solo U         Contact Maximum Voltage Rating In Volts:         1701         Solo U         Contact Maximum Voltage Rating In Volts:         1700         Solo Volts	
Coverall witch4.520 inchesCoverall Witch:2.570 inchesCurrent Type:DcSwitch Type:RelayContact Form Arrangement:2cMounting Configuration:Four tapped holes on back plateAction Type:Time delayRelay Type:Time delayContact Current Type:DcDcMuxinum Voltage Rating In Volts:2s0.0Contact Current Type:DcDcSold Contact Arrangement:2bDcDarting Voltage In Volts:Between 200.0 and 300.0Switch Contact Form Arrangement:2qSold Contact Arrangement:2qSold Contact Arrangement:2qSold Contact Arrangement:2qSold Contact Arrangement:2qSold Contact Form Arrangement:2qContact Maximum Voltage Rating In Volts:2qSold Contact Form Arrangement:2qSold VoltsContact Arrangement:2q<	Overall Depth:
4.520 inches         Overall Width:         2.570 inches         Current Type:         Dc         Switch Type:         Relay         Contact Form Arrangement:         2c         Mounting Configuration:         Four tapped holes on back plate         Action Type:         Time delay         Relay Type:         Time delay         Contact Current Type:         Dc         Maximum Voltage Rating In Volts:         2o0         Coli Current Type:         Dc         Between 200.0 and 300.0         Switch Contact Form Arrangement:         1dpdt         Sould         Sould         Sould         Sould         Switch Contact Form Arrangement:         1dpdt         Sould Sould Sould         Sould Contact Form Arrangement:         1dpdt         Sould Soul	
Overall Width:2.570 inchesCurrent Type:DcSwitch Type:RelayContact Form Arrangement:2cMouting Configuration:Four tapped holes on back plateAction Type:Time delayRelayContact Current Type:DcDcMaximum Voltage Rating In Volts:2b00Switch Contact Form Arrangement:1002c0Maximum Voltage Rating In Volts:2c0.0Switch Contact Arrangement:10pdt2c0.0Switch Contact Form Arrangement:10pdt2c0.0Suitch Contact Arrangement:10pdt2c0.02c	Overall Height:
2.570 inches 2.570 inches Current Type: Co Co Switch Type: Relay Contact Form Arrangement: 2c Mounting Configuration: Four tapped holes on back plate Action Type: Time delay Relay Type: Time delay Relay Type: Time delay Contact Current Type: Co Maximum Voltage Rating In Volts: Co Sou Contact Arrangement: Co Switch Contact Form Arrangement: Co Co Contact Arrangement: Co	4.520 inches
Current Type:         Dc         Switch Type:         Relay         Contact Form Arrangement:         2c         Mounting Configuration:         Four tapped holes on back plate         Action Type:         Time delay         Relay Type:         Time delay         Contact Current Type:         Dc         Maximum Voltage Rating In Volts:         250.0         Coll Current Type:         Dc         Poerating Voltage In Volts:         Between 200.0 and 300.0         Switch Contact Arrangement:         1dpdt         Solo         Contact Maximum Voltage Rating In Volts:         250.0         Switch Contact Arrangement:         1dpdt         Switch Contact Form Arrangement:         2co         Contact Maximum Voltage Rating In Volts:         250.0         Contact Load De Voltage Rating In Volts:         250.0         Continuous Load De Voltage Rating In Volts:         250.0 volts         Continuous Load De Voltage Rating In Volts:         250.0 volts         Contact Arrangement:         20.0	Overall Width:
Dc         Switch Type:         Relay         Contact Form Arrangement:         2c         Mounting Configuration:         Four tapped holes on back plate         Action Type:         Time delay         Relay Type:         Time delay         Contact Current Type:         Dc         Maximum Voltage Rating In Volts:         250.0         Coll Current Type:         Dc         Mich Contact Arrangement:         10c         Switch Contact Form Arrangement:         11dpdt         Solo         Contact Maximum Voltage Rating In Volts:         250.0         Corrent Type:         Dc         Mich Contact Arrangement:         12dpt         Switch Contact Form Arrangement:         12dot         Contact Maximum Voltage Rating In Volts:         250.0         Continuous Load Dc Voltage Rating:         200         Contact Arrangement:         200         Contact Arrangement:         200         Contact Arrangement:         200         Contact Arrangement:	2.570 inches
Switch Type:RelayContact Form Arrangement:2cMounting Configuration:Four tapped holes on back plateAction Type:Time delayRelay Type:Time delayContact Current Type:DcMaximum Voltage Rating In Volts:250.0Coll Current Type:DcOperating Voltage In Volts:Between 200.0 and 300.0Switch Contact Form Arrangement:1qbdtSouth Contact Form Arrangement:2cContact Maximum Voltage Rating In Volts:2so.0South Contact Form Arrangement:1qbdtSouto Contage Rating In Volts:2so.0Contact Maximum Voltage Rating In Volts:2so.0Contact Maximum Voltage Rating In Volts:2so.0Contact Maximum Voltage Rating In Volts:2so.0Continuous Load Dc Voltage Rating:2so.0 voltsContact Arrangement:1dpdtSpecial Features:1dpdtSpecial Features:1dpdtSpecial Features:1dpdtSpecial Features:1dpdtSpecial Features:1dpdtSpecial Features:1dpdtSpecial Features:1dpdtSpecial Features:1dpdtSpecial Features:1dpdtSpecial Features:1dpdt1dpdt1dpdt1dpdt1dpdt1dpdt </td <td>Current Type:</td>	Current Type:
Relay         Contact Form Arrangement:         2c         Mounting Configuration:         Four tapped holes on back plate         Action Type:         Time delay         Relay Type:         Time delay         Contact Current Type:         Dc         Maximum Voltage Rating In Volts:         2s0.0         Coll Current Type:         Dc         Maximum Voltage In Volts:         Between 200.0 and 300.0         Switch Contact Arrangement:         1dpdt         Soul         Contact Maximum Voltage Rating In Volts:         2s0.0         Switch Contact Form Arrangement:         1dpdt         Soulo         Contanuous Load Dc Voltage Rating In Volts:         2s0.0         Contact Maximum Voltage Rating In Volts:         2s0.0         Contact Maximum Voltage Rating In Volts:         2s0.0         Contact Arrangement:         1dpdt         Gontact Arrangement:         1dpdt         Soulo volts         Contact Arrangement:         1dpdt         Special Features:         1dpdt	Dc
Contact Form Arrangement:2cMounting Configuration:Four tapped holes on back plateAction Type:Time delayRelay Type:Time delayContact Current Type:DcMaximum Voltage Rating In Volts:250.0Coll Current Type:DcSoloSolutorent Type:DcSoloSolutorent Type:DcSoloSolutorent Type:DcSoloSolutorent Type:DcSoloSolutorent Type:DcSoloSolutorent Type:DcSoloSolutorent Type:DcSoloSolutorent Type:SoloSolutorent Type:SoloSolutorent Type:SoloSolutorent Corten Arrangement:SoloSoloContact Maximum Voltage Rating In Volts:SoloSoloContinuous Load Dc Voltage Rating In Volts:Solo voltsContact Arrangement:Solo voltsContact Arrangement:Solo voltsSolo voltsSolo voltsSolo voltsContact Arrangement:Solo voltsSolo voltsContact Arrangement:Solo voltsContact Arrangement:Solo voltsSolo voltsSolo voltsSolo voltsSolo voltsSolo volts	Switch Type:
2c         Mounting Configuration:         Four tapped holes on back plate         Action Type:         Time delay         Relay Type:         Time delay         Contact Current Type:         Dc         Maximum Voltage Rating In Volts:         2s0.0         Coll Current Type:         Dc         Mouting Voltage In Volts:         Between 200.0 and 300.0         Switch Contact Arrangement:         1dpdt         Solo         2so.0         Contact Maximum Voltage Rating In Volts:         2so.0         Switch Contact Form Arrangement:         1dpdt         Solo         Solo         Continuous Load Dc Voltage Rating In Volts:         2so.0         Continuous Load Percentage Per Specificationified Tripping Action Time:         9.0         Contact Arrangement:         1dpdt         Generation (Scolad Percentage Per Specificationified Tripping Action Time:         9.0         Contact Arrangement:         1dpdt         Generation (Scolad Percentage Per Specificationified Tripping Action Time:         1dpdt         Special Features:	Relay
Hourting Configuration:Four tapped holes on back plateAction Type:Time delayRelay Type:Time delayContact Current Type:DcMaximum Voltage Rating In Volts:250.0Coll Current Type:DcOrerating Voltage In Volts:Between 200.0 and 300.0Switch Contact Arrangement:1dpdtStoloContact Maximum Voltage Rating In Volts:250.0Between 200.0 and 300.0Switch Contact Arrangement:1dpdtSoloContact Maximum Voltage Rating In Volts:250.0250.0Contact Arrangement:260Contact De Voltage Rating In Volts:250.0250.0Continuous Load De Voltage Rating In Volts:250.0 voltsContinuous Load Percentage Per Specificationified Tripping Action Time:30.0Special Features:Cit-delay operation, calibrated timing headSpecial Features:Special Life:	Contact Form Arrangement:
Four taped holes on back plateAction Type:Time delayRelay Type:Time delayContact Current Type:DcMaximum Voltage Rating In Volts:250.0Coil Current Type:DcOperating Voltage In Volts:Between 200.0 and 300.0Switch Contact Arrangement:1dpdtSwitch Contact Form Arrangement:2cContact Maximum Voltage Rating In Volts:2s0.0Contact Maximum Voltage Rating In Volts:2s0.0Soutch Contact Form Arrangement:1dpdtSoutch Contact Percentage Per Specificationified Tripping Action Time:90.0Contact Arrangement:1dpdtSpecial Features:0,0Contact Arrangement:1dpdtSpecial Features:0,0Special Features:Contact Arrangement:1dpdtSpecial Features:Contact Arrangement:1dpdtSpecial Features:Special Features:Contact Arrangement:1dpdtSpecial Features:Contact Arrangement:Special Features:Contact Arrangement:Special Features:Contact Arrangement:Special Features:Contact Arrangement:Contact Arrangement:Special Features:Contact Arrangement:Contact Arrangement:Special Features:Contact Arrangement:Special Features:Cont	2c
Action Type:Time delayRelay Type:Time delayContact Current Type:DcMaximum Voltage Rating In Volts:250.0Coll Current Type:DcOperating Voltage In Volts:Between 200.0 and 300.0Switch Contact Arrangement:1dpdtSwitch Contact Form Arrangement:250.0Contact Maximum Voltage Rating In Volts:250.0SoloContact Maximum Voltage Rating In Volts:250.0Contact Maximum Voltage Rating In Volts:250.0Continuous Load Dc Voltage Rating In Volts:90.0Contact Arrangement:1dpdtSpecial Features:1dpdtSpecial Features:1dpdtSpecial Features:Contect Arrangement:1dpdtSpecial Features:1dpdtSpecial Features:Contact Arrangement:1dpdtSpecial Features:1dpdtSpecial Features:Contact Arrangement:Contact Arrangement: <td>Mounting Configuration:</td>	Mounting Configuration:
Time delayRelay Type:Time delayContact Current Type:DcMaximum Voltage Rating In Volts:250.0Coil Current Type:DcOperating Voltage In Volts:Between 200.0 and 300.0Switch Contact Arrangement:1dpdtSwitch Contact Form Arrangement:2cContact Maximum Voltage Rating In Volts:250.0SoloContact Maximum Voltage Rating In Volts:2s0.0Contact Maximum Voltage Rating In Volts:250.0Contact Maximum Voltage Rating In Volts:250.0Continuous Load Dc Voltage Rating:250.0 voltsContact Arrangement:40.0Special Features:0.0Contact Arrangement:1dpdtSpecial Features:Off-delay operation, calibrated timing headShelf Life:	Four tapped holes on back plate
Relay Type:Time delayContact Current Type:DcMaxinum Voltage Rating In Volts:250.0Coll Current Type:DcOperating Voltage In Volts:Between 200.0 and 300.0Switch Contact Arrangement:1dpdtSwitch Contact Form Arrangement:2cContact Maximum Voltage Rating In Volts:250.0Contact Maximum Voltage Rating In Volts:250.0Continuous Load Dc Voltage Rating:250.0 voltsContinuous Load Percentage Per Specificationified Tripping Action Time:9.0Contact Arrangement:1dpdtSpecial Features:Off-delay operation, calibrated timing headShelf Life:	Action Type:
Time delay Contact Current Type: Dc Maximum Voltage Rating In Volts: 250.0 Coil Current Type: Dc Operating Voltage In Volts: Between 200.0 and 300.0 Switch Contact Arrangement: 1dpdt Switch Contact Form Arrangement: 2c Contact Maximum Voltage Rating In Volts: 250.0 Continuous Load Dc Voltage Rating: 250.0 Solutis Continuous Load Percentage Per Specificationified Tripping Action Time: 90.0 Contact Arrangement: 1dpdt Special Features: Off-delay operation, calibrated timing head Shelf Life:	Time delay
Contact Current Type:DcMaximum Voltage Rating In Volts:250.0Coil Current Type:DcOperating Voltage In Volts:Between 200.0 and 300.0Switch Contact Arrangement:1dpdtSwitch Contact Form Arrangement:2cContact Maximum Voltage Rating In Volts:250.0Solo voltsContinuous Load Dc Voltage Rating:250.0 voltsContact Arrangement:1dpdtSpecial Features:9.0Contact Arrangement:9.0Sub Contact Arrangement:9.0Contact Maximum Voltage Rating:9.0Contact Arrangement:9.0Contact Arrangement:9.0Contact Arrangement:9.0Contact Arrangement:1dpdtSpecial Features:Off-delay operation, calibrated timing headShelf Life:	Relay Type:
DcMaximum Voltage Rating In Volts:250.0Coil Current Type:DcOperating Voltage In Volts:Between 200.0 and 300.0Switch Contact Arrangement:1dpdtSwitch Contact Form Arrangement:2cContact Maximum Voltage Rating In Volts:250.0Continuous Load Dc Voltage Rating:250.0 voltsContinuous Load Percentage Per Specificationified Tripping Action Time:90.0Contact Arrangement:1dpdtSpecial Features:Off-delay operation, calibrated timing headShelf Life:	Time delay
Maximum Voltage Rating In Volts:250.0Coil Current Type:DcOperating Voltage In Volts:Between 200.0 and 300.0Switch Contact Arrangement:1dpdtSwitch Contact Form Arrangement:2cContact Maximum Voltage Rating In Volts:250.0Continuous Load Dc Voltage Rating:250.0 voltsContinuous Load Percentage Per Specificationified Tripping Action Time:90.0Special Features:Off-delay operation, calibrated timing headShelf Life:	Contact Current Type:
250.0 Coil Current Type: Dc Operating Voltage In Volts: Between 200.0 and 300.0 Switch Contact Arrangement: 1dpdt Switch Contact Form Arrangement: 2c Contact Maximum Voltage Rating In Volts: 250.0 Continuous Load Dc Voltage Rating: 250.0 volts Continuous Load Percentage Per Specificationified Tripping Action Time: 90.0 Contact Arrangement: 1dpdt Special Features: Off-delay operation, calibrated timing head Shelf Life:	Dc
Coil Current Type:DcOperating Voltage In Volts:Between 200.0 and 300.0Switch Contact Arrangement:1dpdtSwitch Contact Form Arrangement:2cContact Maximum Voltage Rating In Volts:250.0250.0Continuous Load Dc Voltage Rating:250.0 voltsContinuous Load Percentage Per Specificationified Tripping Action Time:90.0Special Features:1dpdtSpecial Features:Off-delay operation, calibrated timing headShelf Life:	Maximum Voltage Rating In Volts:
DcOperating Voltage In Volts:Between 200.0 and 300.0Switch Contact Arrangement:1dpdtSwitch Contact Form Arrangement:2cContact Maximum Voltage Rating In Volts:250.0Continuous Load Dc Voltage Rating:250.0 voltsContinuous Load Percentage Per Specificationified Tripping Action Time:90.0Special Features:Off-delay operation, calibrated timing headShelf Life:	250.0
Operating Voltage In Volts:Between 200.0 and 300.0Switch Contact Arrangement:1dpdtSwitch Contact Form Arrangement:2cContact Maximum Voltage Rating In Volts:250.0Continuous Load Dc Voltage Rating:250.0 voltsContinuous Load Percentage Per Specificationified Tripping Action Time:90.0Contact Arrangement:1dpdtSpecial Features:Off-delay operation, calibrated timing headShelf Life:	Coil Current Type:
Between 200.0 and 300.0 Switch Contact Arrangement: 1dpdt Switch Contact Form Arrangement: 2c Contact Maximum Voltage Rating In Volts: 250.0 Continuous Load Dc Voltage Rating: 250.0 volts Continuous Load Percentage Per Specificationified Tripping Action Time: 90.0 Contact Arrangement: 1dpdt Special Features: Off-delay operation, calibrated timing head Shelf Life:	Dc
Switch Contact Arrangement: 1dpdt Switch Contact Form Arrangement: 2c Contact Maximum Voltage Rating In Volts: 250.0 Continuous Load Dc Voltage Rating: 250.0 volts Continuous Load Percentage Per Specificationified Tripping Action Time: 90.0 Contact Arrangement: 1dpdt Special Features: Off-delay operation, calibrated timing head Shelf Life:	Operating Voltage In Volts:
1dpdtSwitch Contact Form Arrangement:2cContact Maximum Voltage Rating In Volts:250.0Continuous Load Dc Voltage Rating:250.0 voltsContinuous Load Percentage Per Specificationified Tripping Action Time:90.0Contact Arrangement:1dpdtSpecial Features:Off-delay operation, calibrated timing headShelf Life:	Between 200.0 and 300.0
Switch Contact Form Arrangement:2cContact Maximum Voltage Rating In Volts:250.0Continuous Load Dc Voltage Rating:250.0 voltsContinuous Load Percentage Per Specificationified Tripping Action Time:90.0Contact Arrangement:1dpdtSpecial Features:Off-delay operation, calibrated timing headShelf Life:	Switch Contact Arrangement:
2c Contact Maximum Voltage Rating In Volts: 250.0 Continuous Load Dc Voltage Rating: 250.0 volts Continuous Load Percentage Per Specificationified Tripping Action Time: 90.0 Contact Arrangement: 1dpdt Special Features: Off-delay operation, calibrated timing head Shelf Life:	1dpdt
Contact Maximum Voltage Rating In Volts: 250.0 Continuous Load Dc Voltage Rating: 250.0 volts Continuous Load Percentage Per Specificationified Tripping Action Time: 90.0 Contact Arrangement: 1dpdt Special Features: Off-delay operation, calibrated timing head Shelf Life:	Switch Contact Form Arrangement:
250.0 Continuous Load Dc Voltage Rating: 250.0 volts Continuous Load Percentage Per Specificationified Tripping Action Time: 90.0 Contact Arrangement: 1dpdt Special Features: Off-delay operation, calibrated timing head Shelf Life:	2c
Continuous Load Dc Voltage Rating: 250.0 volts Continuous Load Percentage Per Specificationified Tripping Action Time: 90.0 Contact Arrangement: 1dpdt Special Features: Off-delay operation, calibrated timing head Shelf Life:	Contact Maximum Voltage Rating In Volts:
250.0 volts Continuous Load Percentage Per Specificationified Tripping Action Time: 90.0 Contact Arrangement: 1dpdt Special Features: Off-delay operation, calibrated timing head Shelf Life:	250.0
Continuous Load Percentage Per Specificationified Tripping Action Time: 90.0 Contact Arrangement: 1dpdt Special Features: Off-delay operation, calibrated timing head Shelf Life:	Continuous Load Dc Voltage Rating:
90.0 Contact Arrangement: 1dpdt Special Features: Off-delay operation, calibrated timing head Shelf Life:	250.0 volts
Contact Arrangement: 1dpdt Special Features: Off-delay operation, calibrated timing head Shelf Life:	Continuous Load Percentage Per Specificationified Tripping Action Time:
1dpdt <b>Special Features:</b> Off-delay operation, calibrated timing head <b>Shelf Life:</b>	90.0
Special Features: Off-delay operation, calibrated timing head Shelf Life:	Contact Arrangement:
Off-delay operation, calibrated timing head Shelf Life:	1dpdt
Shelf Life:	Special Features:
	Off-delay operation, calibrated timing head
N/a	Shelf Life:
I W a	N/a

## NSN 5999-00-631-3066

Relay-switch - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

T142-n

