

View Online at <https://aerobasegroup.com/nsn/5999-00-642-6228>

Thread Class:

2a

Thread Pitch Diameters:

+0.4151 to 0.4152 inches

Body Style:

Rectangular

Frequency Rating:

1.000 megahertz

Body Length:

11.000 inches

Body Width:

5.000 inches

Individual Section Quantity:

4

Operating Temperature Range:

-54.0 to 85.0 degrees celsius

Mounting Facility Quantity:

6

Voltage Rating:

Not rated

Material And Location:

Any acceptable

Surface Treatment And Location:

Enamel, mil-e-15090, type 3, class 2 case

Input Impedance Rating:

2.200 kilohms

Output Impedance Rating:

Not rated

Frequency Bandwidth:

Not rated

Body Depth:

2.250 inches

Mounting Facility:

Threaded hole

Attenuation In Decibels:

4.000

Signal Delay Method:

Lumped constant

Delay Time Variation Method:

Tapped

Section Delay Time:

9.000 microseconds 2nd section

Segment Quantity Per Section:

3 4th section

Segment Delay Time:

28.600 microseconds 1st section 3rd segment

Delay Time Variation Per Deg Celsius:

Not rated

Pulse Rise Time Rating:

Not rated

Terminal Type And Quantity:

16 tab solder lug

Thread Size And Series/type Designator:

0.190-24 unc

Fsc Application Data:

Radar nonairborne except fire control and guided missileradar nonairborne except fire control and guided missile

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A32100