# NSN 5999-00-644-3412

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-00-644-3412

View Online at https://aerobasegroup.com/nsn/5999-00-644-3-
Thread Class:
2a
Thread Pitch Diameters:
+0.2500/+0.2501 inches
Body Style:
Rectangular
Body Length:
7.000 inches
Body Width:
4.563 inches
Individual Section Quantity:
1
Longest Horizontal Distance Between Mounting Centers:
4.500 inches
Longest Vertical Distance Between Mounting Centers:
2.375 inches
Stud Length:
0.500 inches
Mounting Facility Quantity:
4
Material And Location:
Any acceptable
Surface Treatment And Location:
Any acceptable
Input Impedance Rating:
180.000 ohms
Output Impedance Rating:
180.000 ohms
Body Depth:
3.188 inches
Mounting Facility:
Threaded stud
Mounting Provision Arrangement Style:
Four position rectangular
Signal Delay Method:
Inductance
Delay Time Variation Method:
Tapped
Section Delay Time:
20.300 microseconds single section
Segment Quantity Per Section:
14 single section

# NSN 5999-00-644-3412

Delay Line - Page 2 of 2



## Terminal Type And Quantity:

16 wire leads

## Thread Size And Series/type Designator:

0.164-32 unc

Fsc Application Data:

Radar nonairborne except fire control and guided missile

Shelf Life:

N/a

Unit Of Measure:

--

## Demilitarization:

Yes - demil/mli

Fiig:

A32100