

View Online at <https://aerobasegroup.com/nsn/5999-00-646-9437>

Thread Class:

2a

Thread Pitch Diameters:

+0.1875/+0.1876 inches

Body Style:

Rectangular

Body Length:

3.000 inches

Body Width:

0.750 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

1.500 inches

Operating Temperature Range:

-55.0/+85.0 degrees celsius

Stud Length:

0.470 inches

Mounting Facility Quantity:

2

Voltage Rating:

200.000 pounds per hour wet

Material And Location:

Any acceptable

Surface Treatment And Location:

Painted body

Input Impedance Rating:

800.000 ohms

Output Impedance Rating:

800.000 ohms

Frequency Bandwidth:

320.0 kilohertz

Body Depth:

0.750 inches

Mounting Facility:

Threaded stud

Mounting Provision Arrangement Style:

2 position in-line

Attenuation In Decibels:

1.000

Signal Delay Method:

Inductance

Section Delay Time:

1.500 microseconds single section

Pulse Rise Time Rating:

1.0 microseconds

Terminal Type And Quantity:

3 wire hook

Thread Size And Series/type Designator:

0.138-32 unc

Fsc Application Data:

Radar nonairborne except fire control and guided missile

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A32100