

View Online at <https://aerobasegroup.com/nsn/5999-00-646-9777>

**Thread Class:**

2b

**Thread Pitch Diameters:**

+0.0960/+0.0990 inches

**Body Style:**

Rectangular

**Bushing Length:**

0.328 inches

**Body Length:**

4.120 inches

**Body Width:**

0.938 inches

**Individual Section Quantity:**

1

**Longest Horizontal Distance Between Mounting Centers:**

3.844 inches

**Longest Vertical Distance Between Mounting Centers:**

0.344 inches

**Operating Temperature Range:**

-55.0/+100.0 degrees celsius

**Mounting Facility Quantity:**

4

**Voltage Rating:**

20.000 volts

**Material And Location:**

Any acceptable

**Surface Treatment And Location:**

Any acceptable

**Input Impedance Rating:**

3.900 kilohms

**Output Impedance Rating:**

3.900 kilohms

**Body Depth:**

0.620 inches

**Mounting Facility:**

Threaded bushing

**Mounting Provision Arrangement Style:**

Four position rectangular

**Signal Delay Method:**

Lumped constant

**Section Delay Time:**

9.700 microseconds single section

**Pulse Rise Time Rating:**

2.5 microseconds

**Terminal Type And Quantity:**

3 wire hook

**Thread Size And Series/type Designator:**

0.112-40 unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A32100