# NSN 5999-00-646-9777

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-00-646-9777

## Thread Class:

2b

**Thread Pitch Diameters:** 

+0.0960/+0.0990 inches

## Body Style:

Rectangular

#### Bushing Length:

0.328 inches

#### **Body Length:**

4.120 inches

#### **Body Width:**

0.938 inches

#### Individual Section Quantity:

1

## Longest Horizontal Distance Between Mounting Centers:

3.844 inches

## Longest Vertical Distance Between Mounting Centers:

0.344 inches

#### **Operating Tempurature Range:**

-55.0/+100.0 degrees celsius

# **Mounting Facility Quantity:**

4

#### Voltage Rating:

20.000 volts

#### Material And Location:

Any acceptable

#### Surface Treatment And Location:

Any acceptable

#### Input Impedance Rating:

3.900 kilohms

#### **Output Impedance Rating:**

3.900 kilohms

#### **Body Depth:**

0.620 inches

#### **Mounting Facility:**

Threaded bushing

#### Mounting Provision Arrangement Style:

Four position rectangular

#### Signal Delay Method:

Lumped constant

#### Section Delay Time:

9.700 microseconds single section

# NSN 5999-00-646-9777

Delay Line - Page 2 of 2



## Pulse Rise Time Rating:

2.5 microseconds

## Terminal Type And Quantity:

3 wire hook

## Thread Size And Series/type Designator:

0.112-40 unc

Shelf Life:

N/a

Unit Of Measure:

---

## Demilitarization:

Yes - demil/mli

Fiig:

A32100