NSN 5999-00-647-0573

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-00-647-0573 **Thread Class:** 2a **Thread Pitch Diameters:** +0.0997/+0.1177 inches **Body Style:** Rectangular, front connection **Overall Depth:** 1.998 inches **Body Length:** 0.750 inches **Body Width:** 0.750 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 0.353 inches **Operating Tempurature Range:** -55.0/+100.0 degrees celsius Stud Length: 0.310 inches **Inclosure Type:** Hermetically sealed **Mounting Facility Quantity: Material And Location:** Steel, corrosion resisting **Surface Treatment And Location:** Enamel, gray Input Impedance Rating: 900.000 ohms **Output Impedance Rating:** 900.000 ohms **Body Depth:** 1.688 inches **Mounting Facility:** Threaded stud **Mounting Provision Arrangement Style:** 2 position in-line

Signal Delay Method: Electromechanical **Delay Time Variation Method:**

Variable

NSN 5999-00-647-0573

Delay Line - Page 2 of 2



1.600 microseconds single section

Delay Time Variation Per Deg Celsius:

0.100 microseconds

Pulse Rise Time Rating:

1.0 microseconds

Terminal Type And Quantity:

3 wire hook

Thread Size And Series/type Designator:

0.138-32 unc

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A32100