NSN 5999-00-647-0574

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-00-647-0574

Thread Class:
2a
Thread Pitch Diameters:
+0.1399/+0.1428 inches
Body Style:
Rectangular, top connection
Overall Width:
1.406 inches
Body Length:
4.312 inches
Body Width:
1.000 inches
Individual Section Quantity:
1
Longest Horizontal Distance Between Mounting Centers:
3.312 inches
Operating Tempurature Range:
-55.0/+100.0 degrees celsius
Stud Length:
0.375 inches
Inclosure Type:
Hermetically sealed
Mounting Facility Quantity:
2
Material And Location:
Any acceptable
Surface Treatment And Location:
Any acceptable
Input Impedance Rating:
1.000 kilohms
Output Impedance Rating:
1.000 kilohms
Body Depth:
0.875 inches
Mounting Facility:
Threaded stud
Mounting Provision Arrangement Style:
2 position in-line
Attenuation In Decibels:
0.800
Signal Delay Method:

Inductance

NSN 5999-00-647-0574

Delay Line - Page 2 of 2



	Section	Delay	Time:
--	---------	-------	-------

11.600 microseconds single section

Pulse Rise Time Rating:

2.0 microseconds

Terminal Type And Quantity:

3 pin

Thread Size And Series/type Designator:

0.164-32 unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100