

View Online at <https://aerobasegroup.com/nsn/5999-00-660-9990>

Thread Class:

2a

Thread Pitch Diameters:

+0.1875/+0.1876 inches

Body Style:

Rectangular

Body Length:

1.880 inches

Body Width:

3.750 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

1.375 inches

Longest Vertical Distance Between Mounting Centers:

1.125 inches

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Stud Length:

0.470 inches

Mounting Facility Quantity:

4

Material And Location:

Steel case

Surface Treatment And Location:

Any acceptable

Input Impedance Rating:

1.000 kilohms

Output Impedance Rating:

1.000 kilohms

Frequency Bandwidth:

480.0 kilohertz

Body Depth:

1.630 inches

Mounting Facility:

Threaded stud

Mounting Provision Arrangement Style:

Four position rectangular

Attenuation In Decibels:

3.000

Signal Delay Method:

Inductance

Section Delay Time:

5.000 microseconds single section

Pulse Rise Time Rating:

150.0 nanoseconds

Terminal Type And Quantity:

3 wire hook

Thread Size And Series/type Designator:

0.138-32 unc

Fsc Application Data:

Radar nonairborne except fire control and guided missile

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A32100