

View Online at <https://aerobasegroup.com/nsn/5999-00-665-2098>

**Body Style:**

Rectangular, bracketed

**Hole Diameter:**

0.156 inches

**Overall Length:**

1.750 inches

**Frequency Rating:**

Not rated

**Body Length:**

1.000 inches

**Body Width:**

6.000 inches

**Individual Section Quantity:**

1

**Longest Horizontal Distance Between Mounting Centers:**

4.500 inches

**Longest Vertical Distance Between Mounting Centers:**

1.500 inches

**Operating Temperature Range:**

-40.0 to 75.0 degrees celsius

**Mounting Facility Quantity:**

4

**Voltage Rating:**

Not rated

**Material And Location:**

Any acceptable

**Surface Treatment And Location:**

Enamel, dull gray, metallic case

**Input Impedance Rating:**

150.000 ohms

**Output Impedance Rating:**

150.000 ohms

**Frequency Bandwidth:**

Not rated

**Body Depth:**

6.563 inches

**Mounting Facility:**

Unthreaded hole

**Mounting Provision Arrangement Style:**

Four position rectangular

**Attenuation In Decibels:**

Not rated

**Signal Delay Method:**

Inductance

**Delay Time Variation Method:**

Tapped

**Section Delay Time:**

8.000 microseconds single section

**Segment Quantity Per Section:**

3 single section

**Segment Delay Time:**

3.000 microseconds single section 3rd segment

**Delay Time Variation Per Deg Celsius:**

Not rated

**Pulse Rise Time Rating:**

Not rated

**Terminal Type And Quantity:**

6 tab solder lug

**Test Data Document:**

24446-7408046 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Fsc Application Data:**

Radar nonairborne except fire control and guided missile

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A32100