

View Online at <https://aerobasegroup.com/nsn/5999-00-665-2098>

Body Style:

Rectangular, bracketed

Hole Diameter:

0.156 inches

Overall Length:

1.750 inches

Frequency Rating:

Not rated

Body Length:

1.000 inches

Body Width:

6.000 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

4.500 inches

Longest Vertical Distance Between Mounting Centers:

1.500 inches

Operating Temperature Range:

-40.0 to 75.0 degrees celsius

Mounting Facility Quantity:

4

Voltage Rating:

Not rated

Material And Location:

Any acceptable

Surface Treatment And Location:

Enamel, dull gray, metallic case

Input Impedance Rating:

150.000 ohms

Output Impedance Rating:

150.000 ohms

Frequency Bandwidth:

Not rated

Body Depth:

6.563 inches

Mounting Facility:

Unthreaded hole

Mounting Provision Arrangement Style:

Four position rectangular

Attenuation In Decibels:

Not rated

Signal Delay Method:

Inductance

Delay Time Variation Method:

Tapped

Section Delay Time:

8.000 microseconds single section

Segment Quantity Per Section:

3 single section

Segment Delay Time:

3.000 microseconds single section 3rd segment

Delay Time Variation Per Deg Celsius:

Not rated

Pulse Rise Time Rating:

Not rated

Terminal Type And Quantity:

6 tab solder lug

Test Data Document:

24446-7408046 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Fsc Application Data:

Radar nonairborne except fire control and guided missile

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100