## NSN 5999-00-671-8331



Delay Line - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5999-00-671-8331 **Thread Class:** 2b **Thread Pitch Diameters:** +0.0950 to 0.0990 inches **Body Style:** Rectangular, top connection **Overall Width:** 2.000 inches Frequency Rating: Not rated **Body Length:** 4.125 inches **Body Width:** 1.750 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 3.750 inches **Longest Vertical Distance Between Mounting Centers:** 0.750 inches **Operating Tempurature Range:** -55.0 to 100.0 degrees celsius **Inclosure Type:** Encased **Mounting Facility Quantity:** 4 Voltage Rating: Not rated **Material And Location:** Any acceptable body Input Impedance Rating: 2.200 kilohms **Output Impedance Rating:** 2.200 kilohms Frequency Bandwidth: Not rated **Body Depth:** 1.125 inches **Mounting Facility:** 

Threaded hole **Mounting Provision Arrangement Style:** Four position rectangular

## **NSN 5999-00-671-8331**Delay Line - Page 2 of 2



Attenuation In Decibels:
Not rated
Signal Delay Method:
Inductance
Delay Time Variation Method:
Tapped
Section Delay Time:
30.000 microseconds single section
Segment Quantity Per Section:
3 single section
Segment Delay Time:
9.000 microseconds single section 1st segment
Delay Time Variation Per Deg Celsius:
Not rated
Pulse Rise Time Rating:
3.0 microseconds
Terminal Type And Quantity:
5 wire hook
Thread Size And Series/type Designator:
0.112-40 unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A32100