

View Online at <https://aerobasegroup.com/nsn/5999-00-677-0545>

Thread Class:

2a

Thread Pitch Diameters:

+0.1140 to 0.1170 inches

Body Style:

Rectangular, front connection

Overall Depth:

2.626 inches

Frequency Rating:

Not rated

Body Length:

3.969 inches

Body Width:

1.344 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

0.625 inches

Longest Vertical Distance Between Mounting Centers:

3.500 inches

Operating Temperature Range:

Not rated

Stud Length:

0.438 inches

Mounting Facility Quantity:

4

Voltage Rating:

3.000 volts

Input Impedance Rating:

1.700 kilohms

Output Impedance Rating:

1.700 kilohms

Frequency Bandwidth:

Not rated

Body Depth:

2.188 inches

Mounting Facility:

Threaded stud

Mounting Provision Arrangement Style:

Four position rectangular

Attenuation In Decibels:

0.375

Signal Delay Method:

Lumped constant

Delay Time Variation Method:

Tapped

Section Delay Time:

9.415 microseconds single section

Segment Quantity Per Section:

8 single section

Segment Delay Time:

9.235 microseconds single section all segments

Delay Time Variation Per Deg Celsius:

Not rated

Pulse Rise Time Rating:

Not rated

Terminal Type And Quantity:

11 wire hook

Thread Size And Series/type Designator:

0.138-32 unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100