

View Online at <https://aerobasegroup.com/nsn/5999-00-677-0545>

**Thread Class:**

2a

**Thread Pitch Diameters:**

+0.1140 to 0.1170 inches

**Body Style:**

Rectangular, front connection

**Overall Depth:**

2.626 inches

**Frequency Rating:**

Not rated

**Body Length:**

3.969 inches

**Body Width:**

1.344 inches

**Individual Section Quantity:**

1

**Longest Horizontal Distance Between Mounting Centers:**

0.625 inches

**Longest Vertical Distance Between Mounting Centers:**

3.500 inches

**Operating Temperature Range:**

Not rated

**Stud Length:**

0.438 inches

**Mounting Facility Quantity:**

4

**Voltage Rating:**

3.000 volts

**Input Impedance Rating:**

1.700 kilohms

**Output Impedance Rating:**

1.700 kilohms

**Frequency Bandwidth:**

Not rated

**Body Depth:**

2.188 inches

**Mounting Facility:**

Threaded stud

**Mounting Provision Arrangement Style:**

Four position rectangular

**Attenuation In Decibels:**

0.375

**Signal Delay Method:**

Lumped constant

**Delay Time Variation Method:**

Tapped

**Section Delay Time:**

9.415 microseconds single section

**Segment Quantity Per Section:**

8 single section

**Segment Delay Time:**

9.235 microseconds single section all segments

**Delay Time Variation Per Deg Celsius:**

Not rated

**Pulse Rise Time Rating:**

Not rated

**Terminal Type And Quantity:**

11 wire hook

**Thread Size And Series/type Designator:**

0.138-32 unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A32100