NSN 5999-00-686-7604

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-00-686-7604

Body Style:
Round w/round base
Hole Diameter:
0.250 inches
Overall Depth:
1.695 inches
Flange Diameter:
11.750 inches
Body Diameter:
10.750 inches
Mounting Hole Circle Radius:
5.655 inches
Frequency Rating:
30.000 megahertz
Individual Section Quantity:
1
Operating Tempurature Range:
+80.0/+85.0 degrees celsius
Mounting Facility Quantity:
8
Material And Location:
Aluminum alloy case
Surface Treatment And Location:
Enamel, dull gray, metallic case
Input Impedance Rating:
100.000 ohms
Output Impedance Rating:
100.000 ohms
Frequency Bandwidth:
8500.0 kilohertz
Body Depth:
1.500 inches
Mounting Facility:
Unthreaded hole
Mounting Provision Arrangement Style:
Four position circular
Signal Delay Method:
Inductance
Section Delay Time:
1.428 milliseconds single section
Terminal Type And Quantity:
2 threaded stud and 2 coaxial receptacle

NSN 5999-00-686-7604

Delay Line - Page 2 of 2



Special Features:

With 115v heater unit and thermostat control

Test Data Document:

03538-761623revk drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Fsc Application Data:

Radar nonairborne except fire control and guided missile

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100