

View Online at <https://aerobasegroup.com/nsn/5999-00-686-8641>

Body Style:

Rectangular, bracketed

Hole Diameter:

0.196 inches

Overall Length:

9.500 inches

Frequency Rating:

8.000 megahertz

Body Length:

5.740 inches

Body Width:

2.300 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

9.160 inches

Longest Vertical Distance Between Mounting Centers:

1.500 inches

Operating Temperature Range:

-29.0 to 52.0 degrees celsius

Mounting Facility Quantity:

4

Voltage Rating:

Not rated

Material And Location:

Any acceptable

Surface Treatment And Location:

Enamel w/zinc chromate primer undercoat, case

Input Impedance Rating:

240.000 ohms

Output Impedance Rating:

240.000 ohms

Frequency Bandwidth:

3000.0 kilohertz

Body Depth:

0.940 inches

Mounting Facility:

Unthreaded hole

Mounting Provision Arrangement Style:

Four position rectangular

Attenuation In Decibels:

2.000

Signal Delay Method:

Inductance

Delay Time Variation Method:

Tapped

Section Delay Time:

1.100 microseconds single section

Segment Quantity Per Section:

2 single section

Segment Delay Time:

0.900 microseconds single section 2nd segment

Delay Time Variation Per Deg Celsius:

Not rated

Pulse Rise Time Rating:

0.1 microseconds

Terminal Type And Quantity:

5 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A32100