NSN 5999-00-688-6692

Delay Line - Page 1 of 2

2a

Body Style:



View Online at https://aerobasegroup.com/nsn/5999-00-688-6692

Thread Class:

Cylindrical, end post connection
Overall Length:
2.680 inches
Body Diameter:
2.000 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.500 inches
Frequency Rating:
5.000 megahertz
Adjustment Device Quantity:
1
Adjustment Device Drive Type:
Shaft
Body Length:
1.810 inches
Shaft Style:
Round
Individual Section Quantity:
1
Operating Tempurature Range:
-29.0/+52.0 degrees celsius
Stud Length:
0.100 inches
Mounting Facility Quantity:
1
Material And Location:
Any acceptable
Surface Treatment And Location:
Any acceptable
Any acceptable Input Impedance Rating:
, ,
Input Impedance Rating:
Input Impedance Rating: 500.000 ohms
Input Impedance Rating: 500.000 ohms Output Impedance Rating:
Input Impedance Rating: 500.000 ohms Output Impedance Rating: 500.000 ohms
Input Impedance Rating: 500.000 ohms Output Impedance Rating: 500.000 ohms Frequency Bandwidth:

NSN 5999-00-688-6692Delay Line - Page 2 of 2



Attenuation In Decibels:
2.000
Signal Delay Method:
Inductance
Delay Time Variation Method:
Variable
Section Delay Time:
1.000 microseconds single section
Terminal Type And Quantity:
4 solder stud
Thread Size And Series/type Designator:
0.375-32 unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A32100