

View Online at <https://aerobasegroup.com/nsn/5999-00-699-1371>

Thread Class:

2a

Thread Pitch Diameters:

+0.1141 to 0.1169 inches

Body Style:

Rectangular, top connection

Overall Width:

2.626 inches

Frequency Rating:

Between 300.000 hertz and 15.000 kilohertz

Body Length:

3.969 inches

Body Width:

2.188 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

3.500 inches

Longest Vertical Distance Between Mounting Centers:

0.625 inches

Operating Temperature Range:

Not rated

Stud Length:

0.438 inches

Inclosure Type:

Encased

Mounting Facility Quantity:

4

Voltage Rating:

500.000 volts

Material And Location:

Brass case

Surface Treatment And Location:

Enamel, mil-e-15090, type 1, class 2 case or enamel, mil-e-15090, type 2, class 2 case

Input Impedance Rating:

1.170 kilohms

Output Impedance Rating:

1.170 kilohms

Frequency Bandwidth:

Not rated

Body Depth:

1.344 inches

Mounting Facility:

Threaded stud

Mounting Provision Arrangement Style:

Four position rectangular

Attenuation In Decibels:

34.000

Signal Delay Method:

Transmission line

Delay Time Variation Method:

Tapped

Section Delay Time:

83.925 microseconds single section

Segment Quantity Per Section:

9 single section

Segment Delay Time:

9.325 microseconds single section 6th segment

Delay Time Variation Per Deg Celsius:

Not rated

Pulse Rise Time Rating:

Not rated

Terminal Type And Quantity:

11 wire hook

Thread Size And Series/type Designator:

0.138-32 unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100