

View Online at <https://aerobasegroup.com/nsn/5999-00-699-5476>

Thread Class:

2a

Thread Pitch Diameters:

+0.1141 to 0.1169 inches

Body Style:

Rectangular

Frequency Rating:

Not rated

Body Length:

4.750 inches

Body Width:

1.375 inches

Individual Section Quantity:

2

Longest Horizontal Distance Between Mounting Centers:

3.625 inches

Operating Temperature Range:

Not rated

Stud Length:

0.344 inches

Mounting Facility Quantity:

2

Voltage Rating:

Not rated

Material And Location:

Any acceptable

Surface Treatment And Location:

Any acceptable

Input Impedance Rating:

2.000 kilohms

Output Impedance Rating:

2.000 kilohms

Frequency Bandwidth:

Not rated

Body Depth:

0.750 inches

Mounting Facility:

Threaded stud

Mounting Provision Arrangement Style:

2 position in-line

Attenuation In Decibels:

Not rated

Signal Delay Method:

Lumped constant

Section Delay Time:

300.000 nanoseconds 1st section

Delay Time Variation Per Deg Celsius:

Not rated

Pulse Rise Time Rating:

50.0 nanoseconds

Terminal Type And Quantity:

5 pin

Thread Size And Series/type Designator:

0.138-32 unc

Fsc Application Data:

Radar set fire control nonairborne

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A32100