

View Online at <https://aerobasegroup.com/nsn/5999-00-699-5476>

**Thread Class:**

2a

**Thread Pitch Diameters:**

+0.1141 to 0.1169 inches

**Body Style:**

Rectangular

**Frequency Rating:**

Not rated

**Body Length:**

4.750 inches

**Body Width:**

1.375 inches

**Individual Section Quantity:**

2

**Longest Horizontal Distance Between Mounting Centers:**

3.625 inches

**Operating Temperature Range:**

Not rated

**Stud Length:**

0.344 inches

**Mounting Facility Quantity:**

2

**Voltage Rating:**

Not rated

**Material And Location:**

Any acceptable

**Surface Treatment And Location:**

Any acceptable

**Input Impedance Rating:**

2.000 kilohms

**Output Impedance Rating:**

2.000 kilohms

**Frequency Bandwidth:**

Not rated

**Body Depth:**

0.750 inches

**Mounting Facility:**

Threaded stud

**Mounting Provision Arrangement Style:**

2 position in-line

**Attenuation In Decibels:**

Not rated

**Signal Delay Method:**

Lumped constant

**Section Delay Time:**

300.000 nanoseconds 1st section

**Delay Time Variation Per Deg Celsius:**

Not rated

**Pulse Rise Time Rating:**

50.0 nanoseconds

**Terminal Type And Quantity:**

5 pin

**Thread Size And Series/type Designator:**

0.138-32 unc

**Fsc Application Data:**

Radar set fire control nonairborne

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A32100