

View Online at <https://aerobasegroup.com/nsn/5999-00-712-1482>

**Thread Class:**

2b

**Thread Pitch Diameters:**

+0.1875/+0.1876 inches

**Body Style:**

Rectangular

**Frequency Rating:**

1.000 megahertz

**Adjustment Device Quantity:**

1

**Adjustment Device Drive Type:**

Slotted screw

**Body Length:**

4.875 inches

**Body Width:**

0.500 inches

**Individual Section Quantity:**

1

**Longest Horizontal Distance Between Mounting Centers:**

3.375 inches

**Longest Vertical Distance Between Mounting Centers:**

3.250 inches

**Operating Temperature Range:**

+0.0/+60.0 degrees celsius

**Mounting Facility Quantity:**

4

**Material And Location:**

Any acceptable

**Surface Treatment And Location:**

Any acceptable

**Body Depth:**

4.250 inches

**Mounting Facility:**

Threaded hole

**Mounting Provision Arrangement Style:**

Four position rectangular

**Signal Delay Method:**

Inductance

**Delay Time Variation Method:**

Variable

**Section Delay Time:**

498.200 microseconds single section

**Terminal Type And Quantity:**

5 turret

**Thread Size And Series/type Designator:**

0.138-32 unc

**Fsc Application Data:**

Radar nonairborne except fire control and guided missile

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A32100