

View Online at <https://aerobasegroup.com/nsn/5999-00-712-1482>

Thread Class:

2b

Thread Pitch Diameters:

+0.1875/+0.1876 inches

Body Style:

Rectangular

Frequency Rating:

1.000 megahertz

Adjustment Device Quantity:

1

Adjustment Device Drive Type:

Slotted screw

Body Length:

4.875 inches

Body Width:

0.500 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

3.375 inches

Longest Vertical Distance Between Mounting Centers:

3.250 inches

Operating Temperature Range:

+0.0/+60.0 degrees celsius

Mounting Facility Quantity:

4

Material And Location:

Any acceptable

Surface Treatment And Location:

Any acceptable

Body Depth:

4.250 inches

Mounting Facility:

Threaded hole

Mounting Provision Arrangement Style:

Four position rectangular

Signal Delay Method:

Inductance

Delay Time Variation Method:

Variable

Section Delay Time:

498.200 microseconds single section

Terminal Type And Quantity:

5 turret

Thread Size And Series/type Designator:

0.138-32 unc

Fsc Application Data:

Radar nonairborne except fire control and guided missile

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100