

View Online at <https://aerobasegroup.com/nsn/5999-00-726-4046>

Body Style:

Rectangular

Hole Diameter:

0.111 inches

Frequency Rating:

1.000 kilohertz

Body Length:

3.500 inches

Body Width:

1.000 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

3.125 inches

Operating Temperature Range:

+0.0/+60.0 degrees celsius

Mounting Facility Quantity:

2

Voltage Rating:

20.000 volts

Material And Location:

Plastic, diallyl phthalate, mil-m-14, type sdg case

Surface Treatment And Location:

Any acceptable

Input Impedance Rating:

1.000 kilohms

Output Impedance Rating:

1.000 kilohms

Frequency Bandwidth:

720.0 kilohertz

Body Depth:

0.500 inches

Mounting Facility:

Unthreaded hole

Mounting Provision Arrangement Style:

2 position in-line

Attenuation In Decibels:

2.000

Signal Delay Method:

Inductance

Section Delay Time:

6.000 microseconds single section

Pulse Rise Time Rating:

1.4 microseconds

Terminal Type And Quantity:

3 pin

Fsc Application Data:

Radar nonairborne except fire control and guided missile

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100