## NSN 5999-00-726-4258

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-00-726-4258

View Online at https://aerobasegroup.com/nsn/5999-00-726-4
Thread Class:
2a
Thread Pitch Diameters:
+0.1875/+0.1876 inches
Body Style:
Rectangular
Body Length:
5.500 inches
Body Width:
4.563 inches
Individual Section Quantity:
1
Longest Horizontal Distance Between Mounting Centers:
4.600 inches
Longest Vertical Distance Between Mounting Centers:
2.700 inches
Operating Tempurature Range:
+0.0/+60.0 degrees celsius
Stud Length:
0.423 inches
Mounting Facility Quantity:
4
Material And Location:
Any acceptable
Surface Treatment And Location:
Any acceptable
Frequency Bandwidth:
3600.0 kilohertz
Body Depth:
0.729 inches
Mounting Facility:
Threaded stud
Mounting Provision Arrangement Style:
Four position rectangular
Signal Delay Method:
Inductance
Section Delay Time:
1.464 milliseconds single section
Terminal Type And Quantity:
5 pin
Thread Size And Series/type Designator:

0.138-32 unc

# NSN 5999-00-726-4258

Delay Line - Page 2 of 2



#### **Fsc Application Data:**

Radar nonairborne except fire control and guided missile

Shelf Life:

N/a

Unit Of Measure:

---

### Demilitarization:

Yes - demil/mli

#### Fiig:

A32100