NSN 5999-00-726-4259



Delay Line - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5999-00-726-4259 **Thread Class:** 2a **Thread Pitch Diameters:** +0.1875/+0.1876 inches **Body Style:** Rectangular **Body Length:** 5.500 inches **Body Width:** 4.563 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 4.600 inches **Longest Vertical Distance Between Mounting Centers:** 2.700 inches **Operating Tempurature Range:** +0.0/+60.0 degrees celsius Stud Length: 0.423 inches **Mounting Facility Quantity:** 4 **Material And Location:** Any acceptable **Surface Treatment And Location:** Any acceptable Frequency Bandwidth: 3600.0 kilohertz **Body Depth:** 0.729 inches **Mounting Facility:** Threaded stud **Mounting Provision Arrangement Style:** Four position rectangular **Signal Delay Method:** Inductance **Delay Time Variation Method:**

Tapped **Section Delay Time:**

1.222 milliseconds single section

Terminal Type And Quantity:

5 pin

NSN 5999-00-726-4259

Delay Line - Page 2 of 2



Thread	Size	And	Series/tyne	Designator:
ııııcau	JIZE	Allu	OCI ICS/ LV DC	Designator.

0.138-32 unc

Fsc Application Data:

Radar nonairborne except fire control and guided missile

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

Yes - demil/mli

Fiig:

A32100