

View Online at <https://aerobasegroup.com/nsn/5999-00-726-4276>

Thread Class:

2a

Thread Pitch Diameters:

+0.1875 to 0.1876 inches

Body Style:

Rectangular

Adjustment Device Quantity:

1

Adjustment Device Drive Type:

Slotted screw

Body Length:

5.500 inches

Body Width:

4.562 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

4.600 inches

Longest Vertical Distance Between Mounting Centers:

2.700 inches

Operating Temperature Range:

+0.0 to 60.0 degrees celsius

Stud Length:

0.426 inches

Mounting Facility Quantity:

4

Material And Location:

Steel case

Surface Treatment And Location:

Any acceptable

Frequency Bandwidth:

3600.0 kilohertz

Body Depth:

0.500 inches

Mounting Facility:

Threaded stud

Mounting Provision Arrangement Style:

Four position rectangular

Signal Delay Method:

Lumped constant

Delay Time Variation Method:

Variable

Section Delay Time:

246.100 microseconds single section

Pulse Rise Time Rating:

100.0 nanoseconds

Terminal Type And Quantity:

5 pin

Thread Size And Series/type Designator:

0.138.32 unc

Fsc Application Data:

Radar nonairborne except fire control and guided missile

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A32100