

View Online at <https://aerobasegroup.com/nsn/5999-00-728-4388>

Thread Class:

2a

Thread Pitch Diameters:

+0.2500 to 0.2501 inches

Body Style:

Rectangular

Frequency Rating:

Not rated

Body Length:

9.000 inches

Body Width:

1.500 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

7.000 inches

Longest Vertical Distance Between Mounting Centers:

1.000 inches

Operating Temperature Range:

Not rated

Stud Length:

0.500 inches

Mounting Facility Quantity:

4

Voltage Rating:

3.000 millivolts

Material And Location:

Steel case

Surface Treatment And Location:

Enamel, dull gray, metallic case

Input Impedance Rating:

1.000 kilohms

Output Impedance Rating:

1.000 kilohms

Frequency Bandwidth:

Not rated

Body Depth:

2.250 inches

Mounting Facility:

Threaded stud

Mounting Provision Arrangement Style:

Four position rectangular

Attenuation In Decibels:

14.400

Signal Delay Method:

Lumped constant

Delay Time Variation Method:

Tapped

Section Delay Time:

369.000 microseconds single section

Segment Quantity Per Section:

7 single section

Segment Delay Time:

61.500 microseconds single section 1st segment

Delay Time Variation Per Deg Celsius:

Not rated

Pulse Rise Time Rating:

Not rated

Terminal Type And Quantity:

9 pin

Thread Size And Series/type Designator:

0.164-32 unc

Fsc Application Data:

Radar nonairborne except fire control and guided missile

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100