

View Online at <https://aerobasegroup.com/nsn/5999-00-730-3940>

Thread Class:

2b

Body Style:

Rectangular, top connection

Overall Width:

2.724 inches

Frequency Rating:

Not rated

Body Length:

6.000 inches

Body Width:

2.380 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

1.125 inches

Longest Vertical Distance Between Mounting Centers:

4.000 inches

Operating Temperature Range:

-54.0 to 55.0 degrees celsius

Mounting Facility Quantity:

4

Voltage Rating:

300.000 volts

Material And Location:

Any acceptable

Surface Treatment And Location:

Any acceptable

Input Impedance Rating:

50.000 ohms

Output Impedance Rating:

50.000 ohms

Frequency Bandwidth:

Not rated

Body Depth:

2.000 inches

Mounting Facility:

Threaded hole

Mounting Provision Arrangement Style:

Four position rectangular

Attenuation In Decibels:

Not rated

Signal Delay Method:

Lumped constant

Delay Time Variation Method:

Tapped

Section Delay Time:

2.000 microseconds single section

Segment Quantity Per Section:

10 single section

Segment Delay Time:

200.000 nanoseconds single section all segments

Delay Time Variation Per Deg Celsius:

Not rated

Pulse Rise Time Rating:

150.0 nanoseconds

Terminal Type And Quantity:

12 tab solder lug

Thread Size And Series/type Designator:

0.138-32 unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiiq:

A32100