

View Online at <https://aerobasegroup.com/nsn/5999-00-731-9229>

Thread Class:

2b

Thread Pitch Diameters:

+0.2500/+0.2501 inches

Body Style:

Rectangular

Shaft Diameter:

0.250 inches

Shaft Length:

0.375 inches

Adjustment Device Quantity:

1

Adjustment Device Drive Type:

Shaft

Body Length:

2.125 inches

Body Width:

2.250 inches

Shaft Style:

Round

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

1.625 inches

Longest Vertical Distance Between Mounting Centers:

1.750 inches

Operating Temperature Range:

+0.0/+75.0 degrees celsius

Mounting Facility Quantity:

4

Material And Location:

Aluminum alloy case

Surface Treatment And Location:

Enamel, dull gray, metallic case

Input Impedance Rating:

500.000 ohms

Output Impedance Rating:

500.000 ohms

Frequency Bandwidth:

900.0 kilohertz

Body Depth:

2.500 inches

Step Quantity:

8

Mounting Facility:

Threaded hole

Mounting Provision Arrangement Style:

Four position rectangular

Attenuation In Decibels:

4.000

Signal Delay Method:

Lumped constant

Delay Time Variation Method:

Adjustable

Delay Time Per Step:

500.000 nanoseconds

Section Delay Time:

4.000 microseconds single section

Terminal Type And Quantity:

2 connector, receptacle

Special Features:

Two solder lug terminals for external resistor

Thread Size And Series/type Designator:

0.164-32 unc

Fsc Application Data:

Radar nonairborne except fire control and guided missile

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100