

View Online at <https://aerobasegroup.com/nsn/5999-00-753-0914>

Thread Class:

2b

Thread Pitch Diameters:

+0.1000 to 0.1001 inches

Body Style:

Rectangular

Adjustment Device Quantity:

1

Adjustment Device Drive Type:

Slotted screw

Body Length:

Between 4.469 inches and 4.500 inches

Body Width:

Between 1.969 inches and 2.000 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

Between 1.734 inches and 1.766 inches

Shortest Horizontal Distance Between Mounting Centers:

Between 0.859 inches and 0.891 inches

Longest Vertical Distance Between Mounting Centers:

Between 4.234 inches and 4.266 inches

Shortest Vertical Distance Between Mounting Centers:

Between 2.109 inches and 2.141 inches

Operating Temperature Range:

+0.0 to 60.0 degrees celsius

Voltage Rating:

15.000 volts

Input Impedance Rating:

200.000 ohms

Output Impedance Rating:

200.000 ohms

Frequency Bandwidth:

Not rated

Body Depth:

Between 0.562 inches and 0.625 inches

Mounting Facility:

Threaded hole

Mounting Provision Arrangement Style:

Four position diamond

Attenuation In Decibels:

3.000

Signal Delay Method:

Lumped constant

Delay Time Variation Method:

Variable

Section Delay Time:

3.000 microseconds single section

Delay Time Variation Per Deg Celsius:

Not rated

Pulse Rise Time Rating:

0.1 microseconds

Terminal Type And Quantity:

4 wire hook

Thread Size And Series/type Designator:

0.112-40 unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A32100