## NSN 5999-00-755-4636



Delay Line - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5999-00-755-4636 **Body Style:** Rectangular **Hole Diameter:** 0.138 inches Frequency Rating: 3.000 megahertz **Body Length:** 4.000 inches **Body Width:** 1.000 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 2.750 inches **Operating Tempurature Range:** -29.0 to 60.0 degrees celsius **Mounting Facility Quantity:** 2 **Voltage Rating:** Not rated Input Impedance Rating: 1000.000 ohms **Output Impedance Rating:** 1000.000 ohms Frequency Bandwidth: Not rated **Body Depth:** 

1.875 inches

**Mounting Facility:** 

Threaded insert

**Mounting Provision Arrangement Style:** 

2 position in-line

**Attenuation In Decibels:** 

Not rated

**Signal Delay Method:** 

Inductance

**Delay Time Variation Method:** 

Tapped

**Section Delay Time:** 

1.300 microseconds single section

**Segment Quantity Per Section:** 

4 single section

## NSN 5999-00-755-4636

Delay Line - Page 2 of 2



## **Segment Delay Time:**

1.300 microseconds single section 4th segment

**Delay Time Variation Per Deg Celsius:** 

Not rated

**Pulse Rise Time Rating:** 

0.1 microseconds

**Terminal Type And Quantity:** 

6 tab solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

Yes - demil/mli

Fiig:

A32100