

View Online at <https://aerobasegroup.com/nsn/5999-00-762-7289>

**Thread Class:**

2a

**Thread Pitch Diameters:**

+0.1875 to 0.1876 inches

**Body Style:**

Rectangular

**Frequency Rating:**

Not rated

**Body Length:**

1.875 inches

**Body Width:**

1.625 inches

**Individual Section Quantity:**

1

**Longest Horizontal Distance Between Mounting Centers:**

1.438 inches

**Longest Vertical Distance Between Mounting Centers:**

1.188 inches

**Operating Temperature Range:**

+0.0 to 60.0 degrees celsius

**Stud Length:**

0.375 inches

**Mounting Facility Quantity:**

4

**Voltage Rating:**

Not rated

**Material And Location:**

Any acceptable

**Surface Treatment And Location:**

Enamel, mil-e-15090, type 1, class 2 case

**Input Impedance Rating:**

500.000 ohms

**Output Impedance Rating:**

Not rated

**Frequency Bandwidth:**

360.0 kilohertz

**Body Depth:**

2.750 inches

**Mounting Facility:**

Threaded stud

**Mounting Provision Arrangement Style:**

Four position rectangular

**Attenuation In Decibels:**

6.000

**Signal Delay Method:**

Inductance

**Section Delay Time:**

21.700 microseconds single section

**Delay Time Variation Per Deg Celsius:**

Not rated

**Pulse Rise Time Rating:**

1.0 microseconds

**Terminal Type And Quantity:**

3 wire hook

**Thread Size And Series/type Designator:**

0.138-32 unc

**Fsc Application Data:**

Radar nonairborne except fire control and guided missile

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A32100