

View Online at <https://aerobasegroup.com/nsn/5999-00-763-3830>

Thread Class:

2a

Thread Pitch Diameters:

+0.1875 to 0.1876 inches

Body Style:

Rectangular

Frequency Rating:

Not rated

Body Length:

2.750 inches

Body Width:

4.375 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

2.125 inches

Longest Vertical Distance Between Mounting Centers:

1.750 inches

Operating Temperature Range:

+0.0 to 50.0 degrees celsius

Stud Length:

0.375 inches

Mounting Facility Quantity:

4

Voltage Rating:

Not rated

Material And Location:

Any acceptable

Surface Treatment And Location:

Any acceptable

Input Impedance Rating:

50.000 ohms

Output Impedance Rating:

50.000 ohms

Frequency Bandwidth:

900.0 kilohertz

Body Depth:

2.375 inches

Mounting Facility:

Threaded stud

Mounting Provision Arrangement Style:

Four position rectangular

Attenuation In Decibels:

Not rated

Signal Delay Method:

Lumped constant

Delay Time Variation Method:

Tapped

Section Delay Time:

20.300 microseconds single section

Segment Quantity Per Section:

13 single section

Segment Delay Time:

2.900 microseconds single section 7th segment

Delay Time Variation Per Deg Celsius:

Not rated

Pulse Rise Time Rating:

Not rated

Terminal Type And Quantity:

16 wire leads

Thread Size And Series/type Designator:

0.138-32 unc

Fsc Application Data:

Radar nonairborne except fire control and guided missile

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100