

View Online at <https://aerobasegroup.com/nsn/5999-00-769-7407>

**Thread Class:**

2b

**Thread Pitch Diameters:**

+0.1875/+0.1876 inches

**Body Style:**

Rectangular

**Body Length:**

4.000 inches

**Body Width:**

2.000 inches

**Individual Section Quantity:**

1

**Longest Horizontal Distance Between Mounting Centers:**

3.500 inches

**Longest Vertical Distance Between Mounting Centers:**

1.505 inches

**Operating Temperature Range:**

-55.0/+75.0 degrees celsius

**Mounting Facility Quantity:**

4

**Material And Location:**

Any acceptable

**Surface Treatment And Location:**

Enamel, dull gray, metallic case

**Input Impedance Rating:**

1.000 kilohms

**Output Impedance Rating:**

1.000 kilohms

**Body Depth:**

3.000 inches

**Mounting Facility:**

Threaded hole

**Mounting Provision Arrangement Style:**

Four position rectangular

**Signal Delay Method:**

Lumped constant

**Delay Time Variation Method:**

Tapped

**Section Delay Time:**

12.000 microseconds single section

**Segment Quantity Per Section:**

5 single section

**Segment Delay Time:**

2.000 microseconds single section all segments

**Pulse Rise Time Rating:**

250.0 nanoseconds

**Terminal Type And Quantity:**

7 tab solder lug

**Thread Size And Series/type Designator:**

0.138-32 unc

**Fsc Application Data:**

Radar nonairborne except fire control and guided missile

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A32100