

View Online at <https://aerobasegroup.com/nsn/5999-00-769-7407>

Thread Class:

2b

Thread Pitch Diameters:

+0.1875/+0.1876 inches

Body Style:

Rectangular

Body Length:

4.000 inches

Body Width:

2.000 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

3.500 inches

Longest Vertical Distance Between Mounting Centers:

1.505 inches

Operating Temperature Range:

-55.0/+75.0 degrees celsius

Mounting Facility Quantity:

4

Material And Location:

Any acceptable

Surface Treatment And Location:

Enamel, dull gray, metallic case

Input Impedance Rating:

1.000 kilohms

Output Impedance Rating:

1.000 kilohms

Body Depth:

3.000 inches

Mounting Facility:

Threaded hole

Mounting Provision Arrangement Style:

Four position rectangular

Signal Delay Method:

Lumped constant

Delay Time Variation Method:

Tapped

Section Delay Time:

12.000 microseconds single section

Segment Quantity Per Section:

5 single section

Segment Delay Time:

2.000 microseconds single section all segments

Pulse Rise Time Rating:

250.0 nanoseconds

Terminal Type And Quantity:

7 tab solder lug

Thread Size And Series/type Designator:

0.138-32 unc

Fsc Application Data:

Radar nonairborne except fire control and guided missile

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A32100