NSN 5999-00-772-5707

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-00-772-5707 **Body Style:** Rectangular, bracketed **Hole Diameter:** 0.250 inches **Overall Length:** 8.000 inches Frequency Rating: Not rated **Body Length:** 6.560 inches **Body Width:** 1.000 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 7.250 inches **Longest Vertical Distance Between Mounting Centers:** 2.500 inches **Operating Tempurature Range:** Not rated **Mounting Facility Quantity: Voltage Rating:** Not rated **Surface Treatment And Location:** Enamel, mil-e-15090, type 1, class 2 Input Impedance Rating: Not rated **Output Impedance Rating:** Not rated Frequency Bandwidth: Not rated **Body Depth:**

6.000 inches **Mounting Facility:** Unthreaded hole **Mounting Provision Arrangement Style:** Four position rectangular **Attenuation In Decibels:** 10.000 **Signal Delay Method:** Inductance

NSN 5999-00-772-5707

Delay Line - Page 2 of 2



Delay Time Variation Method:
Tapped
Section Delay Time:
7.850 microseconds single section
Segment Quantity Per Section:
3 single section
Segment Delay Time:
7.850 microseconds single section 3rd segment
Pulse Rise Time Rating:
Not rated
Terminal Type And Quantity:
5 tab solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A32100