

View Online at <https://aerobasegroup.com/nsn/5999-00-773-2801>

Thread Class:

2b

Thread Pitch Diameters:

+0.2500 to 0.2501 inches

Body Style:

Round, open, wire lug

Body Diameter:

Between 7.688 inches and 7.781 inches

Frequency Rating:

Not rated

Body Inside Diameter:

Between 4.359 inches and 4.437 inches

Individual Section Quantity:

1

Operating Temperature Range:

+0.0 to 75.0 degrees celsius

Mounting Facility Quantity:

12

Voltage Rating:

Not rated

Material And Location:

Steel case

Surface Treatment And Location:

Tin plate, mil-t-10727, type 1 or 2 case

Input Impedance Rating:

20.000 kilohms

Output Impedance Rating:

20.000 kilohms

Frequency Bandwidth:

Not rated

Body Depth:

Between 1.313 inches and 1.406 inches

Mounting Facility:

Threaded hole

Attenuation In Decibels:

22.000

Signal Delay Method:

Lumped constant

Delay Time Variation Method:

Tapped

Section Delay Time:

254.500 microseconds single section

Segment Quantity Per Section:

8 single section

Segment Delay Time:

59.700 microseconds single section 2nd segment

Delay Time Variation Per Deg Celsius:

Not rated

Pulse Rise Time Rating:

Not rated

Terminal Type And Quantity:

10 wire hook

Thread Size And Series/type Designator:

0.164-32 unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100