

View Online at <https://aerobasegroup.com/nsn/5999-00-773-2801>

**Thread Class:**

2b

**Thread Pitch Diameters:**

+0.2500 to 0.2501 inches

**Body Style:**

Round, open, wire lug

**Body Diameter:**

Between 7.688 inches and 7.781 inches

**Frequency Rating:**

Not rated

**Body Inside Diameter:**

Between 4.359 inches and 4.437 inches

**Individual Section Quantity:**

1

**Operating Temperature Range:**

+0.0 to 75.0 degrees celsius

**Mounting Facility Quantity:**

12

**Voltage Rating:**

Not rated

**Material And Location:**

Steel case

**Surface Treatment And Location:**

Tin plate, mil-t-10727, type 1 or 2 case

**Input Impedance Rating:**

20.000 kilohms

**Output Impedance Rating:**

20.000 kilohms

**Frequency Bandwidth:**

Not rated

**Body Depth:**

Between 1.313 inches and 1.406 inches

**Mounting Facility:**

Threaded hole

**Attenuation In Decibels:**

22.000

**Signal Delay Method:**

Lumped constant

**Delay Time Variation Method:**

Tapped

**Section Delay Time:**

254.500 microseconds single section

**Segment Quantity Per Section:**

8 single section

**Segment Delay Time:**

59.700 microseconds single section 2nd segment

**Delay Time Variation Per Deg Celsius:**

Not rated

**Pulse Rise Time Rating:**

Not rated

**Terminal Type And Quantity:**

10 wire hook

**Thread Size And Series/type Designator:**

0.164-32 unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A32100