

View Online at <https://aerobasegroup.com/nsn/5999-00-774-6469>

Thread Class:

2a

Thread Pitch Diameters:

+0.1875/+0.1876 inches

Body Style:

Rectangular

Body Length:

2.250 inches

Body Width:

0.625 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

1.750 inches

Stud Length:

0.375 inches

Mounting Facility Quantity:

2

Surface Treatment And Location:

Enamel, dull gray, metallic body

Input Impedance Rating:

1.300 kilohms

Output Impedance Rating:

1.300 kilohms

Frequency Bandwidth:

360.0 kilohertz

Body Depth:

1.000 inches

Mounting Facility:

Threaded stud

Mounting Provision Arrangement Style:

2 position in-line

Signal Delay Method:

Inductance

Section Delay Time:

5.000 microseconds single section

Pulse Rise Time Rating:

1.0 microseconds

Terminal Type And Quantity:

3 tab solder lug

Thread Size And Series/type Designator:

0.138-32 unc

Fsc Application Data:

Radar nonairborne except fire control and guided missile

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100