

View Online at <https://aerobasegroup.com/nsn/5999-00-775-2393>

Thread Class:

2a

Thread Pitch Diameters:

+0.2500 to 0.2501 inches

Body Style:

Rectangular

Frequency Rating:

Not rated

Body Length:

1.000 inches

Body Width:

1.000 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

0.594 inches

Longest Vertical Distance Between Mounting Centers:

0.594 inches

Operating Temperature Range:

+0.0 to 60.0 degrees celsius

Stud Length:

0.375 inches

Mounting Facility Quantity:

4

Voltage Rating:

Not rated

Material And Location:

Any acceptable

Surface Treatment And Location:

Enamel, mil-e-15090, type 1, class 2 case

Input Impedance Rating:

500.000 ohms

Output Impedance Rating:

Not rated

Frequency Bandwidth:

360.0 kilohertz

Body Depth:

2.125 inches

Mounting Facility:

Threaded stud

Mounting Provision Arrangement Style:

Four position rectangular

Attenuation In Decibels:

6.000

Signal Delay Method:

Inductance

Section Delay Time:

6.400 microseconds single section

Delay Time Variation Per Deg Celsius:

Not rated

Pulse Rise Time Rating:

1.0 microseconds

Terminal Type And Quantity:

3 wire hook

Thread Size And Series/type Designator:

0.112-40 unc

Fsc Application Data:

Radar nonairborne except fire control and guided missile

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100