

View Online at <https://aerobasegroup.com/nsn/5999-00-779-9409>

Thread Class:

2b

Thread Pitch Diameters:

+0.2800/+0.2801 inches

Body Style:

Rectangular

Body Length:

5.750 inches

Body Width:

3.750 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

5.250 inches

Longest Vertical Distance Between Mounting Centers:

3.250 inches

Operating Temperature Range:

-55.0/+85.0 degrees celsius

Mounting Facility Quantity:

4

Material And Location:

Plastic body

Surface Treatment And Location:

Any acceptable

Input Impedance Rating:

800.000 ohms

Output Impedance Rating:

800.000 ohms

Frequency Bandwidth:

30000.0 kilohertz

Body Depth:

0.400 inches

Mounting Facility:

Threaded hole

Mounting Provision Arrangement Style:

Four position rectangular

Attenuation In Decibels:

1.000

Signal Delay Method:

Lumped constant

Delay Time Variation Method:

Tapped

Section Delay Time:

24.650 microseconds single section

Segment Quantity Per Section:

17 single section

Segment Delay Time:

1.450 microseconds single section all segments

Terminal Type And Quantity:

19 wire leads

Thread Size And Series/type Designator:

0.112-40 unc

Fsc Application Data:

Data display groups communcations central

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100