NSN 5999-00-779-9409



Delay Line - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5999-00-779-9409 **Thread Class:** 2b **Thread Pitch Diameters:** +0.2800/+0.2801 inches **Body Style:** Rectangular **Body Length:** 5.750 inches **Body Width:** 3.750 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 5.250 inches **Longest Vertical Distance Between Mounting Centers:** 3.250 inches **Operating Tempurature Range:** -55.0/+85.0 degrees celsius **Mounting Facility Quantity: Material And Location:** Plastic body **Surface Treatment And Location:** Any acceptable Input Impedance Rating: 800.000 ohms **Output Impedance Rating:** 800.000 ohms Frequency Bandwidth: 30000.0 kilohertz **Body Depth:** 0.400 inches **Mounting Facility:** Threaded hole **Mounting Provision Arrangement Style:** Four position rectangular **Attenuation In Decibels:** 1.000

Signal Delay Method: Lumped constant

Delay Time Variation Method:

Tapped

NSN 5999-00-779-9409

Delay Line - Page 2 of 2



24.650 microseconds single section

Segment Quantity Per Section:

17 single section

Segment Delay Time:

1.450 microseconds single section all segments

Terminal Type And Quantity:

19 wire leads

Thread Size And Series/type Designator:

0.112-40 unc

Fsc Application Data:

Data display groups communcations central

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

Yes - demil/mli

Fiig:

A32100