

View Online at <https://aerobasegroup.com/nsn/5999-00-781-7177>

**Thread Class:**

2b

**Thread Pitch Diameters:**

+0.2800/+0.2801 inches

**Body Style:**

Rectangular

**Body Length:**

6.000 inches

**Body Width:**

4.000 inches

**Individual Section Quantity:**

1

**Longest Horizontal Distance Between Mounting Centers:**

6.250 inches

**Longest Vertical Distance Between Mounting Centers:**

3.250 inches

**Operating Temperature Range:**

-55.0/+85.0 degrees celsius

**Mounting Facility Quantity:**

6

**Material And Location:**

Plastic body

**Surface Treatment And Location:**

Any acceptable

**Input Impedance Rating:**

800.000 ohms

**Output Impedance Rating:**

800.000 ohms

**Frequency Bandwidth:**

30000.0 kilohertz

**Body Depth:**

0.900 inches

**Mounting Facility:**

Threaded hole

**Mounting Provision Arrangement Style:**

Four position rectangular

**Attenuation In Decibels:**

1.000

**Signal Delay Method:**

Lumped constant

**Delay Time Variation Method:**

Tapped

**Section Delay Time:**

25.000 microseconds single section

**Segment Quantity Per Section:**

25 single section

**Segment Delay Time:**

1.000 microseconds single section all segments

**Terminal Type And Quantity:**

27 wire leads

**Thread Size And Series/type Designator:**

0.112-40 unc

**Fsc Application Data:**

Data display groups communications central

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A32100