

View Online at <https://aerobasegroup.com/nsn/5999-00-781-9435>

Thread Class:

2b

Thread Pitch Diameters:

+0.2500 to 0.2501 inches

Body Style:

Rectangular

Frequency Rating:

2.750 megahertz

Body Length:

3.375 inches

Body Width:

7.250 inches 7.250 inches

Individual Section Quantity:

22

Longest Horizontal Distance Between Mounting Centers:

3.000 inches 3.000 inches

Longest Vertical Distance Between Mounting Centers:

5.000 inches 5.000 inches

Operating Temperature Range:

Not rated

Mounting Facility Quantity:

44

Voltage Rating:

Not rated

Material And Location:

Steel case steel case

Surface Treatment And Location:

Enamel coating over zinc coating case enamel coating over zinc coating case

Input Impedance Rating:

10.000 kilohms 10.000 kilohms

Output Impedance Rating:

10.000 kilohms 10.000 kilohms

Frequency Bandwidth:

Not rated

Body Depth:

3.000 inches 3.000 inches

Mounting Facility:

Threaded hole threaded hole

Mounting Provision Arrangement Style:

Four position rectangular four position rectangular

Attenuation In Decibels:

3.000 3.000

Signal Delay Method:

Lumped constantlumped constant

Delay Time Variation Method:

Tappedtapped

Section Delay Time:

752.000 microseconds all sections752.000 microseconds all sections

Segment Quantity Per Section:

10 2nd section10 2nd section

Segment Delay Time:

94.000 microseconds 1st section 10th segment

Delay Time Variation Per Deg Celsius:

Not rated

Pulse Rise Time Rating:

Not rated

Terminal Type And Quantity:

26 tab solder lug

Thread Size And Series/type Designator:

0.164-32 unc

Fsc Application Data:

Sonar set

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A32100