## NSN 5999-00-786-4622

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-00-786-4622

#### Body Style:

Round w/square base

#### Hole Diameter:

0.125 inches

## **Overall Depth:**

3.125 inches

## **Overall Length:**

1.250 inches

#### Overall Width:

1.250 inches

### Body Diameter:

1.000 inches

## Frequency Rating:

12.000 megahertz

## Individual Section Quantity:

Longest Horizontal Distance Between Mounting Centers:

1

#### 1.000 inches

### Longest Vertical Distance Between Mounting Centers:

1.000 inches

#### **Operating Tempurature Range:**

+0.0/+85.0 degrees celsius

#### Mounting Facility Quantity:

4

## Material And Location:

Brass case

## Surface Treatment And Location:

Nickel plated case

## Input Impedance Rating:

383.000 ohms

## Output Impedance Rating:

383.000 ohms

## Frequency Bandwidth:

4000.0 kilohertz

## Body Depth:

2.500 inches

## Mounting Facility:

Unthreaded hole

## Mounting Provision Arrangement Style:

Four position rectangular

#### Attenuation In Decibels:

42.000

# NSN 5999-00-786-4622

Delay Line - Page 2 of 2



Signal Delay Method:

Lumped constant

Section Delay Time:

4.000 microseconds single section

Terminal Type And Quantity:

1 turret and 1 connector, receptacle

Fsc Application Data:

Radar nonairborne except fire control and guided missile

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

Yes - demil/mli

Fiig:

A32100