NSN 5999-00-786-4622

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-00-786-4622

Body Style:
Round w/square base
Hole Diameter:
0.125 inches
Overall Depth:
3.125 inches
Overall Length:
1.250 inches
Overall Width:
1.250 inches
Body Diameter:
1.000 inches
Frequency Rating:
12.000 megahertz
Individual Section Quantity:
1
Longest Horizontal Distance Between Mounting Centers:
1.000 inches
Longest Vertical Distance Between Mounting Centers:
1.000 inches
Operating Tempurature Range:
+0.0/+85.0 degrees celsius
Mounting Facility Quantity:
4
Material And Location:
Brass case
Surface Treatment And Location:
Nickel plated case
Input Impedance Rating:
383.000 ohms
Output Impedance Rating:
383.000 ohms
Frequency Bandwidth:
4000.0 kilohertz
Body Depth:
2.500 inches
Mounting Facility:
Unthreaded hole
Mounting Provision Arrangement Style:
Four position rectangular
Attenuation In Decibels:

42.000

NSN 5999-00-786-4622

Delay Line - Page 2 of 2

Yes - demil/mli

Fiig: A32100



Signal Delay Method:
Lumped constant
Section Delay Time:
4.000 microseconds single section
Terminal Type And Quantity:
1 turret and 1 connector, receptacle
Fsc Application Data:
Radar nonairborne except fire control and guided missile
Shelf Life:
N/a
Unit Of Measure:
Demilitarization: