## NSN 5999-00-786-6623

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-00-786-6623

| Body Style:   |
|---|
| Rectangular   |
| Hole Diameter:  |
| 0.125 inches  |
| Frequency Rating:                                     |
| 1.000 megahertz                                       |
| Body Length:  |
| 2.875 inches  |
| Body Width:   |
| 0.938 inches  |
| Individual Section Quantity:                          |
| 2   |
| Longest Horizontal Distance Between Mounting Centers: |
| 2.500 inches  |
| Operating Tempurature Range:                          |
| +0.0/+65.0 degrees celsius                            |
| Mounting Facility Quantity:                           |
| 2   |
| Material And Location:                                |
| Plastic body  |
| Surface Treatment And Location:                       |
| Any acceptable  |
| Input Impedance Rating:                               |
| 120.000 ohms  |
| Output Impedance Rating:                              |
| 120.000 ohms  |
| Body Depth:   |
| 0.375 inches  |
| Mounting Facility:                                    |
| Unthreaded hole                                       |
| Mounting Provision Arrangement Style:                 |
| 2 position in-line                                    |
| Attenuation In Decibels:                              |
| 0.700   |
| Signal Delay Method:                                  |
| Lumped constant                                       |
| Section Delay Time:                                   |
| 500.000 nanoseconds all sections                      |
| Terminal Type And Quantity:                           |
| 6 wire leads  |
| Fsc Application Data:                                 |

Sonar communications set

## NSN 5999-00-786-6623

Delay Line - Page 2 of 2



| _ |   |            |   |    |    |
|---|---|------------|---|----|----|
| • | n | <b>0</b> 1 | • | 12 | e: |
|   |   |            |   |    |    |

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100