

View Online at <https://aerobasegroup.com/nsn/5999-00-786-9003>

Thread Class:

2a

Shaft Diameter:

0.125 inches

Shaft Length:

0.562 inches

Frequency Rating:

60.000 hertz

Adjustment Device Quantity:

1

Adjustment Device Drive Type:

Shaft

Shaft Style:

Round, slotted

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

1.500 inches

Longest Vertical Distance Between Mounting Centers:

0.625 inches

Operating Temperature Range:

-55.0/+85.0 degrees celsius

Stud Length:

0.375 inches

Mounting Facility Quantity:

4

Voltage Rating:

350.000 volts

Material And Location:

Steel case

Surface Treatment And Location:

Enamel, tt-e529 class a, case

Input Impedance Rating:

560.000 ohms

Step Quantity:

9

Mounting Facility:

Threaded stud

Mounting Provision Arrangement Style:

Four position rectangular

Attenuation In Decibels:

1.000

Signal Delay Method:

Inductance

Delay Time Variation Method:

Adjustable

Delay Time Per Step:

6.100 nanoseconds

Section Delay Time:

54.900 nanoseconds single section

Pulse Rise Time Rating:

180.0 nanoseconds

Terminal Type And Quantity:

5 wire hook

Thread Size And Series/type Designator:

0.138-32 unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A32100