NSN 5999-00-804-3588

Electronic Shielding Gasket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-00-804-3588

| Cross Sectional Shape: |
|---|
| Mesh and composition |
| Hole Diameter: |
| 0.020 inches |
| Overall Length: |
| 4.438 inches |
| Tempurature Rating: |
| -65.0 degrees fahrenheit and 175.0 degrees fahrenheit |
| Overall Width: |
| 3.625 inches |
| Minor Width: |
| 0.125 inches |
| Aperture Width: |
| 2.625 inches |
| Aperture Length: |
| 3.438 inches |
| Center To Center Distance Between Bolt Holes Along Width: |
| 1.531 inches |
| Center To Center Distance Between Bolt Holes Along Length: |
| 1.250 inches |
| Outside Edge To Bolt Hole Center Distance Along Width: |
| 0.281 inches |
| Outside Edge To Bolt Hole Center Distance Along Length: |
| 0.281 inches |
| Cross-sectional Height: |
| 0.062 inches |
| Minor Height: |
| 0.062 inches |
| Bolt Hole Quantity: |
| 10 |
| Environmental Protection Material Location: |
| Around rf shielding gasket |
| Material: |
| Rubber chloroprene class cr environmental seal |
| Material Specification: |
| Qq-n-281, cl a federal specification single material response emi/rfi conductor |
| Style Designator: |
| Non-circular |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

--

NSN 5999-00-804-3588

Electronic Shielding Gasket - Page 2 of 2



Demilitarization:

No

Fiig:

A032a0

Mil-std (military Standard):

Mil-r-6130a spec.